



MTP1000 & MTPmini

Modular Test Platform

Key Features

- All-in-one benchtop test platform with multi-functional blades
- One intuitive and easy to use software for all the Blades
- Ethernet or USB connectivity
- SCPI compliant remote control for simple automation
- Limitless scalability

Ultimate Scalability and Versatility Built-in

With the modular architecture, you can set up a testing platform with just the right number of blades to suit your current requirement while future proofing yourself with the potential to add more.

The available blades are: **LaserBlade-ITLA**, **LaserBlade-DFB**, **VOABlade**, **SwitchBlade**, **PowerBlade-I**, **PowerBlade-T**, **PolBlade**, **O2EBlade**, **SLEDBlade** & **TrayBlade**.

Efficient Use of Space

MTP1000 platform lets you make the most of your testing bench space by housing up to 9 blades of your choice. This enables you to replace a tower of stacked equipment with just one mainframe.

19-inch Rack Mountability

The MTP1000 mainframe with the optional rack mounting brackets is compatible with any 19-inch rack for easy integration into your testing set up.

Full-size or Mini, Your Choice

Just want a couple of Blades to put in a cramped space? **MTPmini** lets you harness all the flexibility and connectivity in a small two-module chassis, with a built-in touch screen for stand-alone operation.

Remote Control

MTP1000 comes equipped with USB and ethernet connectivity, so that you can control and monitor the instrument remotely from a different location. You can also talk to the instrument using SCPI commands to automate the testing procedures, this will save you valuable time.

Intuitive and Functional Software Interface

The control software for MTP1000, Test Instrument Manager (TIM), uses graphical representation of the instrument for intuitive control of connected units. The same software controls different types of Blade modules, to save you time and effort in control and set up of the test platform.

General Specifications	MTP1000	MTPmini
Dimensions (HxWxD)	220 mm x 480 mm x 500 mm (8.7" x 18.9" x 19.7")	115 mm x 222 mm x 332 mm (4.53" x 8.74" x 13.07")
Weight	18 kg (39.7 lbs)	3.5 kg (7.72 lbs)
PC interface method	USB 2.0 Ethernet	USB 2.0 Ethernet
Operating system requirement	Windows 7, 8 or 10 (32 or 64 bit)	Windows 7, 8 or 10 (32 or 64 bit)
Power supply	~100 - 240 V 50/60 Hz 500 W	~110 - 240 V 50/60 Hz 100 W
Operating temperature range	5 °C to 45 °C (41 °F to 113 °F)	5 °C to 45 °C (41 °F to 113 °F)
Storage temperature range	-40 °C to 70 °C (-40 °F to 158 °F)	-40 °C to 70 °C (-40 °F to 158 °F)

To find out more, get in touch with us today.

Coherent Solutions Ltd
Unit A, 28 Canaveral Drive
Rosedale, Auckland 0632
New Zealand



General enquiries: info@coherent-solutions.com
 Technical support: support@coherent-solutions.com
 Tel: +64 9 478 4849
 Fax: +64 9 478 4851
www.coherent-solutions.com

- www.linkedin.com/company/coherent-solutions-ltd
- www.facebook.com/CoherentSolutionsLtd
- www.youtube.com/CoherentSolutionsLtd
- www.weibo.com/CoherentSolutionsLtd
- i.youku.com/CoherentSolutionsLtd